



OREO LINEA DOWN L1514 BLINE 940 0
CAIXA ALIMENTAÇÃO TRIMLESS 2I L120 HF 1014-2014 W
 ARCHITECTURAL LIGHTING


90420L151000000
977600W



Light distribution



L=1514mm



L=118mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care
Mounting Type: Suspended
Control Gear Included: Yes
Control Gear: 24V transformer

OREO LINEA DOWN L1514 BLINE 940 0

CHARACTERISTICS

Luminaire Type: Straight line luminaire
Luminaire Module: Individual
Insulation Class: III
Ingress Protection (IP): 40
Ambient Temperature Range (°C):]-5, 25[
Pre-wiring / Through-wiring Included: 1,5m long transparent current supply cable
Warranty (Years): 5

MATERIALS

Body Material: Extruded aluminium profile
Finishing: Epoxy polyester powder coated
Colour: Sahara (0)
Glow-wire Resistance (°C): 850

OPTICAL SYSTEM

Optical System: bLINE - Opal diffuser
Light Distribution: Direct
Beam Angle (°): 18

TECHNICAL DATA

Light Source: LED

Input Power (W): 16

Power Factor (λ): 1

Luminaire Luminous Flux (lm): 956

Luminaire Efficacy (lm/W): 60

Unified Glare Rating (UGR): <22

LED Lifetime - Rated Median Useful Life: 60.000h @ L80, B10, Ta 25°C

CCT - Correlated Colour Temperature (K): 4000

Photobiological safety according to IEC 62471: Not Available

Colour Rendering Index (CRI): >90

Chromaticity Tolerance (MacAdam step): <3

This Product Contains a Light Source of Energy Efficiency Class: F

LED Module Forward Voltage Range (VF): 24V DC

Input luminaire current (mA): 681

DIMENSIONS

L - Length (mm): 1514

W - Width (mm): 35

H - Height (mm): 35

Net Weight (kg): 1.6

CAIXA ALIMENTAÇÃO TRIMLESS 2I L120 HF 1014-2014 W

CHARACTERISTICS

Insulation Class: II

Ingress Protection (IP): 20

Ambient Temperature Range (°C):]-5, 25[

Warranty (Years): 5

MATERIALS

Colour: White (W)

**OREO LINEA DOWN L1514 BLINE 940 0
CAIXA ALIMENTAÇÃO TRIMLESS 2I L120 HF 1014-2014 W****90420L151000000
977600W**ARCHITECTURAL LIGHTING

TECHNICAL DATA**Input Power (W):** 35**Input Driver Voltage:** 220-240V-50/60Hz**Power Supply Dimming:** ON/OFF**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <40**Inrush Current (A):** 30**Pulse Duration (µs):** 180**DIMENSIONS****L - Length (mm):** 118**W - Width (mm):** 58**H - Height (mm):** 40**D - Diameter (mm):** 120**D - Recess Dimensions (mm):** 122x62**NOTES**

- Current supply cable/suspension with 1500 mm included;
- For Tunable White and RGB White versions, the product must include a transparent current supply cable;
- The noise level is 20 dB, lower than the typical ambient sound levels recorded in environments such as libraries and reading rooms.