




**HOLI SQ /C MINI Q115 LIGHT+ DALI 840 W/B**

ARCHITECTURAL LIGHTING

**90269L006HW00B0****Light distribution**

L=115mm

**PRODUCT DESCRIPTION**

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

**Mounting Type:** Surface mounted

**Control Gear Included:** Yes

**Control Gear:** LED driver 220-240VAC-50/60Hz

**HOLI SQ /C MINI Q115 LIGHT+ DALI 840 W/B****CHARACTERISTICS**

**Luminaire Type:** Square downlight

**Luminaire Module:** Individual

**Insulation Class:** I

**Ingress Protection (IP):** 40

**Ambient Temperature Range (°C):** ]-5, 25[

**Warranty (Years):** 5

**Current Supply Cable Entry Point:** Back

**MATERIALS**

**Body Material:** Steel sheet

**Frame Material:** Steel sheet

**Finishing:** Epoxy polyester powder coated

**Colour:** White (W)/Black (B)

**Glow-wire Resistance (°C):** 650

**OPTICAL SYSTEM**

**Optical System:** LIGHT+ - Opal diffuser

**Light Distribution:** Direct

**Beam Angle (°):** 94

**TECHNICAL DATA**

**Light Source:** LED

**Input Power (W):** 8

**Input Driver Voltage:** 220-240V-50/60Hz

**Power Factor (λ):** 0,7

**Luminaire Luminous Flux (lm):** 930

**Luminaire Efficacy (lm/W):** 116

**Unified Glare Rating (UGR):** <22

**LED Lifetime - Rated Median Useful Life:** 72.000h @ L70, B10, Ta 25°C

**CCT - Correlated Colour Temperature (K):** 4000

**Colour Rendering Index (CRI):** >80

**Chromaticity Tolerance (MacAdam step):** <3

**This Product Contains a Light Source of Energy Efficiency Class:** D

**LED Module Forward Voltage Range (VF):** 33

**Power Supply Dimming:** DALI 2

**Central Battery Emergency Lighting System (VDC):** 176-280

**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <38

**Inrush Current (A):** 30

**Pulse Duration (µs):** 100

**DIMENSIONS**

**L - Length (mm):** 115

**W - Width (mm):** 115

**H - Height (mm):** 120

**Net Weight (kg):** 1