




OREO LINEA UP L2014 BLINE RGBW 5

ARCHITECTURAL LIGHTING

90399L201050R00



Light distribution



L=2014mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

Mounting Type: Suspended

Control Gear Included: No

Input luminaire current (mA): 1520

LED Lifetime - Rated Median Useful Life [Indirect]: 50.000h @ L80, B10, Ta 25°C

CCT - Correlated Colour Temperature (K) [Indirect]: RGBW

Colour Rendering Index (CRI) [Indirect]: >80

Chromaticity Tolerance (MacAdam step) [Indirect]: <3

This Product contains a Light Source of Energy Efficiency Class [Indirect]: G

OREO LINEA UP L2014 BLINE RGBW 5

CHARACTERISTICS

Luminaire Type: Straight line luminaire

Luminaire Module: Individual

Insulation Class: III

Ingress Protection (IP): 40

Ambient Temperature Range (°C):]-5, 25[

Warranty (Years): 5

DIMENSIONS

L - Length (mm): 2014

W - Width (mm): 35

H - Height (mm): 35

Net Weight (kg): 2

MATERIALS

Body Material: Extruded aluminium profile

Finishing: Epoxy polyester powder coated

Colour: Old Rose (5)

Glow-wire Resistance (°C): 850

NOTES

- Current supply cable/suspension with 1500 mm included;
- To complete the product it is necessary to order the ceiling rose separately;
- For Tunable White and RGB White versions, the product must include a transparent current supply cable.

OPTICAL SYSTEM

Optical System: bLINE - Opal diffuser

Light Distribution: Direct

Beam Angle (°): 18

TECHNICAL DATA

Input Power (W): 36

Power Factor (λ): 1

Photobiological safety according to IEC 62471: Not Available