

TALEA GLARE L2278 BLINE 830 B

TUBULAR LUMINAIRES

90428L1800B0300**Light distribution**

L=2278mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

Mounting Type: Surface mounted, Suspended, Wall mounted

Control Gear Included: No

TALEA GLARE L2278 BLINE 830 B**CHARACTERISTICS**

Luminaire Type: Straight line luminaire

Insulation Class: III

Ingress Protection (IP): 40

Ambient Temperature Range (°C):]-5, 25[

Warranty (Years): 5

Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Extruded aluminium profile

Finishing: Epoxy polyester powder coated

Colour: Black (B)

Glow-wire Resistance (°C): 960

OPTICAL SYSTEM

Optical System: bLINE - Opal diffuser

Light Distribution: Direct

Beam Angle (°): 183

TECHNICAL DATA

Light Source: LED

Input Power (W): 32

Power Factor (λ): 1

Luminaire Luminous Flux (lm): 4435

Luminaire Efficacy (lm/W): 139

Unified Glare Rating (UGR): <19

LED Lifetime - Rated Median Useful Life: 80.000h @ L90, B10, Ta 25°C

CCT - Correlated Colour Temperature (K): 3000

Colour Rendering Index (CRI): >80

Chromaticity Tolerance (MacAdam step): <3

LED Module Forward Voltage Range (VF): 33,1

Input luminaire current (mA): 960

DIMENSIONS

L - Length (mm): 2278

D - Diameter (mm): 100

Net Weight (kg): 6.7

NOTES

- To complete the product it is necessary to order the suspension, the current supply cable and ceiling rose. Please order separately.