


**TALEA GLARE L2558 BLINE K3 840 B**

TUBULAR LUMINAIRES

**90428L1900B3000****Light distribution**

L=2558mm

**PRODUCT DESCRIPTION**

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

**Mounting Type:** Surface mounted, Suspended, Wall mounted

**Control Gear Included:** No

**TALEA GLARE L2558 BLINE K3 840 B****CHARACTERISTICS**

**Luminaire Type:** Straight line luminaire

**Insulation Class:** III

**Ingress Protection (IP):** 40

**Ambient Temperature Range (°C):** ]5, 25[

**Warranty (Years):** 5

**Current Supply Cable Entry Point:** Back

**Luminaire Luminous Flux (lm):** 5405

**Luminaire Efficacy (lm/W):** 150

**Emergency Unit:** 3

**Unified Glare Rating (UGR):** <19

**LED Lifetime - Rated Median Useful Life:** 80.000h @ L90, B10, Ta 25°C

**CCT - Correlated Colour Temperature (K):** 4000

**Colour Rendering Index (CRI):** >80

**Chromaticity Tolerance (MacAdam step):** <3

**LED Module Forward Voltage Range (VF):** 33,1

**Input luminaire current (mA):** 1080

**DIMENSIONS**

**L - Length (mm):** 2558

**D - Diameter (mm):** 100

**Net Weight (kg):** 7.3

**MATERIALS**

**Body Material:** Extruded aluminium profile

**Finishing:** Epoxy polyester powder coated

**Colour:** Black (B)

**Glow-wire Resistance (°C):** 960

**OPTICAL SYSTEM**

**Optical System:** bLINE - Opal diffuser

**Light Distribution:** Direct

**Beam Angle (°):** 183

**TECHNICAL DATA**

**Light Source:** LED

**Input Power (W):** 36

**Power Factor (λ):** 1

**NOTES**

- To complete the product it is necessary to order the suspension, the current supply cable and ceiling rose. Please order separately.