



# REBA 65 D/I INT L2524 ASYM DALI 830 HO

ALUMINIUM PROFILE SYSTEMS

90534L009HW0300



## Light distribution



L=2524mm

## PRODUCT DESCRIPTION

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care  
**Mounting Type:** Suspended  
**Control Gear Included:** No

## REBA 65 D/I INT L2524 ASYM DALI 830 HO

### CHARACTERISTICS

**Luminaire Type:** Straight line luminaire  
**Luminaire Module:** Individual, Middle (MID), Start / End (SRT/END)  
**Insulation Class:** I  
**Ingress Protection (IP):** 40  
**Ambient Temperature Range (°C):** ]-5, 25[  
**Warranty (Years):** 5  
**Current Supply Cable Entry Point:** Back

### MATERIALS

**Body Material:** Extruded aluminium profile  
**Finishing:** Epoxy polyester powder coated  
**Colour:** White (W)  
**Glow-wire Resistance (°C):** 850

### OPTICAL SYSTEM

**Optical System:** ASYM - Asymmetric diffuser  
**Light Distribution:** Direct / Indirect  
**Beam Angle (°):** 54

### TECHNICAL DATA

**Light Source:** LED  
**Input Power (W):** 127

**Input Driver Voltage:** 220-240V-50/60Hz

**Power Factor (λ):** 0,96

**Luminaire Luminous Flux (lm):** 10690

**Luminaire Efficacy (lm/W):** 84

**Unified Glare Rating (UGR):** <19

**LED Lifetime - Rated Median Useful Life:** 80.000h @ L90, B10, Ta 25°C

**CCT - Correlated Colour Temperature (K):** 3000

**Colour Rendering Index (CRI):** >80

**Chromaticity Tolerance (MacAdam step):** <3

**LED Module Forward Voltage Range (VF):** 32,2

**Power Supply Dimming:** DALI 2

**Central Battery Emergency Lighting System (VDC):** 176-280

**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <17

**Inrush Current (A):** 18

**Pulse Duration (µs):** 180

**This Product contains a Light Source of Energy Efficiency Class [Indirect]:** B

### DIMENSIONS

**L - Length (mm):** 2524  
**W - Width (mm):** 62  
**H - Height (mm):** 71  
**Net Weight (kg):** 5.34

### NOTES

- The indirect light diffuser is included on the product;
- To complete the product it is necessary to order the inner profile, suspension kit, current supply cable and ceiling rose. Please order separately.