

CONCEPT O 35 D1853 BFLEX HF 840 R

ARCHITECTURAL LIGHTING

90539L040ER0000



Light distribution



PRODUCT DESCRIPTION

Application Areas: Architectural, Offices, Hotels and residential, Public spaces, Retail, Art and Culture, Education, Health and care

Mounting Type: Surface mounted, Suspended

Control Gear Included: Yes

Control Gear: LED driver 220-240VAC-50/60Hz

Input Driver Voltage: 220-240V-50/60Hz

Power Factor (λ): 0,99

Luminaire Luminous Flux (lm): 16506

Luminaire Efficacy (lm/W): 99

Unified Glare Rating (UGR): <22

LED Lifetime - Rated Median Useful Life: 70.000h @ L90, B10, Ta 25°C

CCT - Correlated Colour Temperature (K): 4000

Colour Rendering Index (CRI): >80

Chromaticity Tolerance (MacAdam step): <3

LED Module Forward Voltage Range (VF): 24V DC

Power Supply Dimming: ON/OFF

Maximum of Luminaires by Magnetic Circuit Breaker B16: <30

CONCEPT O 35 D1853 BFLEX HF 840 R

CHARACTERISTICS

Luminaire Type: Circular luminaire

Insulation Class: I

Ingress Protection (IP): 40

Ambient Temperature Range (°C):]-5, 25[

Warranty (Years): 5

Current Supply Cable Entry Point: Back

DIMENSIONS

H - Height (mm): 56

D - Diameter (mm): 1853

Net Weight (kg): 14.6

MATERIALS

Body Material: Extruded aluminium profile

Finishing: Epoxy polyester powder coated

Colour: Rusty chain (R)

Glow-wire Resistance (°C): 960

OPTICAL SYSTEM

Optical System: bFLEX - Opal diffuser

Light Distribution: Direct

Beam Angle (°): 112

NOTES

- For suspended version it is necessary to order suspension, current supply cable and ceiling rose separately;
- For diameter above D1494 mm the product is composed by multiple modules;
- To help simulate the product in the space, please check CONFIGURATOR.INDELAGUEGROUP.COM;
- The noise level is 20 dB, lower than the typical ambient sound levels recorded in environments such as libraries and reading rooms.

TECHNICAL DATA

Light Source: LED

Input Power (W): 166