


# CONCEPT S 35 45° RIGHT D2569 DALI 840 N SRT

ARCHITECTURAL LIGHTING

90544R007HN0049



## Light distribution



L=983mm

## PRODUCT DESCRIPTION

**Application Areas:** Architectural, Offices, Hotels and residential, Public spaces, Retail, Art and Culture, Education, Health and care

**Mounting Type:** Surface mounted, Suspended

**Control Gear Included:** Yes

**Control Gear:** LED driver 220-240VAC-50/60Hz

## CONCEPT S 35 45° RIGHT D2569 DALI 840 N SRT

### CHARACTERISTICS

**Luminaire Type:** Curved luminaire 1/8 45°

**Luminaire Module:** Start (SRT)

**Luminaire Orientation:** Right

**Insulation Class:** I

**Ingress Protection (IP):** 40

**Ambient Temperature Range (°C):** ]-5, 25[

**Warranty (Years):** 5

**Current Supply Cable Entry Point:** Back

### MATERIALS

**Body Material:** Extruded aluminium profile

**Finishing:** Epoxy polyester powder coated

**Colour:** Jungle (N)

**Glow-wire Resistance (°C):** 960

### OPTICAL SYSTEM

**Optical System:** bFLEX - Opal diffuser

**Light Distribution:** Direct

**Beam Angle (°):** 111

### TECHNICAL DATA

**Light Source:** LED

**Input Power (W):** 32

**Input Driver Voltage:** 220-240V-50/60Hz

**Power Factor (λ):** 0,95

**Luminaire Luminous Flux (lm):** 2889

**Luminaire Efficacy (lm/W):** 90

**LED Lifetime - Rated Median Useful Life:** 70.000h @ L90, B10, Ta 25°C

**CCT - Correlated Colour Temperature (K):** 4000

**Colour Rendering Index (CRI):** >80

**Chromaticity Tolerance (MacAdam step):** <3

**LED Module Forward Voltage Range (VF):** 24V DC

**Power Supply Dimming:** DALI 2

**Maximum of luminaires by Magnetic Circuit Breaker B16:** <45

### DIMENSIONS

**L - Length (mm):** 983

**W - Width (mm):** 55

**H - Height (mm):** 56

**D - Diameter (mm):** 2569

**Net Weight (kg):** 2.8

### NOTES

- To complete the product it is necessary to order the bFLEX diffuser and the start kit. Please order separately;
- To complete the product it is necessary to order the bFLEX diffuser, start kit and body connector kit. Please order separately;
- For suspended version it is necessary to order the suspension, the current supply cable and the ceiling rose. Please order separately;
- Dimensions do not include start kit. To complete the line add 26 mm to the length;
- Create your own configurations on [CONFIGURATOR.INDEL AGUEGROUP.COM](http://CONFIGURATOR.INDEL AGUEGROUP.COM);
- The noise level is 20 dB, lower than the typical ambient sound levels

**CONCEPT S 35 45° RIGHT D2569 DALI 840 N SRT**  
ARCHITECTURAL LIGHTING

**90544R007HN0049**

---

recorded in environments such as libraries and reading rooms.