

CONCEPT S 35 45° RIGHT D2926 HF 830 B MID/END

ARCHITECTURAL LIGHTING

90544R008EB0398



Light distribution



L=1120mm

PRODUCT DESCRIPTION

Application Areas: Architectural, Offices, Hotels and residential, Public spaces, Retail, Art and Culture, Education, Health and care

Mounting Type: Surface mounted, Suspended

Control Gear Included: Yes

Control Gear: LED driver 220-240VAC-50/60Hz

CONCEPT S 35 45° RIGHT D2926 HF 830 B MID/END

CHARACTERISTICS

Luminaire Type: Curved luminaire 1/8 45°

Luminaire Module: Middle / End (MID/END)

Luminaire Orientation: Right

Insulation Class: I

Ingress Protection (IP): 40

Ambient Temperature Range (°C):]-5, 25[

Warranty (Years): 5

Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Extruded aluminium profile

Finishing: Epoxy polyester powder coated

Colour: Black (B)

Glow-wire Resistance (°C): 960

OPTICAL SYSTEM

Optical System: bFLEX - Opal diffuser

Light Distribution: Direct

Beam Angle (°): 111

TECHNICAL DATA

Light Source: LED

Input Power (W): 36

Input Driver Voltage: 220-240V-50/60Hz

Power Factor (λ): 0,96

Luminaire Luminous Flux (lm): 3205

Luminaire Efficacy (lm/W): 89

LED Lifetime - Rated Median Useful Life: 70.000h @ L90, B10, Ta 25°C

CCT - Correlated Colour Temperature (K): 3000

Colour Rendering Index (CRI): >80

Chromaticity Tolerance (MacAdam step): <3

LED Module Forward Voltage Range (VF): 24V DC

Power Supply Dimming: ON/OFF

Maximum of luminaires by Magnetic Circuit Breaker B16: <45

DIMENSIONS

L - Length (mm): 1120

W - Width (mm): 55

H - Height (mm): 56

D - Diameter (mm): 2926

Net Weight (kg): 3.1

NOTES

- To complete the product it is necessary to order the bFLEX diffuser and the start kit. Please order separately;
- To complete the product it is necessary to order the bFLEX diffuser, start kit and body connector kit. Please order separately;
- For suspended version it is necessary to order the suspension, the current supply cable and the ceiling rose. Please order separately;
- Dimensions do not include start kit. To complete the line add 26 mm to the length;
- Create your own configurations on CONFIGURATOR.INDEL AGUEGROUP.COM;
- The noise level is 20 dB, lower than the typical ambient sound levels

CONCEPT S 35 45° RIGHT D2926 HF 830 B MID/END

90544R008EB0398

ARCHITECTURAL LIGHTING

recorded in environments such as libraries and reading rooms.