

## CONCEPT S 35 90° RIGHT D1494 HF 830 7 MID/END

ARCHITECTURAL LIGHTING

90545R008E70398



### Light distribution



L=1057mm

### PRODUCT DESCRIPTION

**Application Areas:** Architectural, Offices, Hotels and residential, Public spaces, Retail, Art and Culture, Education, Health and care

**Mounting Type:** Surface mounted, Suspended

**Control Gear Included:** Yes

**Control Gear:** LED driver 220-240VAC-50/60Hz

### CONCEPT S 35 90° RIGHT D1494 HF 830 7 MID/END

#### CHARACTERISTICS

**Luminaire Type:** Curved luminaire 1/4 90°

**Luminaire Module:** Middle / End (MID/END)

**Luminaire Orientation:** Right

**Insulation Class:** I

**Ingress Protection (IP):** 40

**Ambient Temperature Range (°C):** ]-5, 25[

**Warranty (Years):** 5

**Current Supply Cable Entry Point:** Back

#### MATERIALS

**Body Material:** Extruded aluminium profile

**Finishing:** Epoxy polyester powder coated

**Colour:** Copper (7)

**Glow-wire Resistance (°C):** 960

#### OPTICAL SYSTEM

**Optical System:** bFLEX - Opal diffuser

**Light Distribution:** Direct

**Beam Angle (°):** 111

#### TECHNICAL DATA

**Light Source:** LED

**Input Power (W):** 36

**Input Driver Voltage:** 220-240V-50/60Hz

**Power Factor (λ):** 0,96

**Luminaire Luminous Flux (lm):** 3205

**Luminaire Efficacy (lm/W):** 89

**LED Lifetime - Rated Median Useful Life:** 70.000h @ L90, B10, Ta 25°C

**CCT - Correlated Colour Temperature (K):** 3000

**Colour Rendering Index (CRI):** >80

**Chromaticity Tolerance (MacAdam step):** <3

**LED Module Forward Voltage Range (VF):** 24V DC

**Power Supply Dimming:** ON/OFF

**Maximum of luminaires by Magnetic Circuit Breaker B16:** <45

#### DIMENSIONS

**L - Length (mm):** 1057

**W - Width (mm):** 55

**H - Height (mm):** 56

**D - Diameter (mm):** 1494

**Net Weight (kg):** 3.2

#### NOTES

- To complete the product it is necessary to order the bFLEX diffuser and the start kit. Please order separately;
- To complete the product it is necessary to order the bFLEX diffuser, start kit and body connector kit. Please order separately;
- For suspended version it is necessary to order the suspension, the current supply cable and the ceiling rose. Please order separately;
- Dimensions do not include start kit. To complete the line add 26 mm to the length;
- Create your own configurations on [CONFIGURATOR.INDEL AGUEGROUP.COM](http://CONFIGURATOR.INDEL AGUEGROUP.COM);
- The noise level is 20 dB, lower than the typical ambient sound levels

**CONCEPT S 35 90° RIGHT D1494 HF 830 7 MID/END**  
ARCHITECTURAL LIGHTING

**90545R008E70398**

---

recorded in environments such as libraries and reading rooms.