



TTP 50 360 VRT L1270 TOP 840 B

TUBULAR LUMINAIRES

90555L1200B0000**Light distribution****PRODUCT DESCRIPTION****Application Areas:** Public spaces, Industry, Outside**Mounting Type:** Suspended**Control Gear Included:** No**TTP 50 360 VRT L1270 TOP 840 B****CHARACTERISTICS****Luminaire Type:** Straight line luminaire**Luminaire Module:** Individual**Insulation Class:** III**Ingress Protection (IP):** 40**Ambient Temperature Range (°C):**]-10, 25[**Warranty (Years):** 5**Current Supply Cable Entry Point:** End cap**Luminaire Luminous Flux (lm):** 2685**Luminaire Efficacy (lm/W):** 117**Unified Glare Rating (UGR):** <22**LED Lifetime - Rated Median Useful Life:** 70.000h @ L80, B10, Ta 25°C**CCT - Correlated Colour Temperature (K):** 4000**Colour Rendering Index (CRI):** >80**Chromaticity Tolerance (MacAdam step):** <3**This Product Contains a Light Source of Energy Efficiency Class:** D**LED Module Forward Voltage Range (VF):** 21,5-26,4**Input luminaire current (mA):** 940**DIMENSIONS****L - Length (mm):** 1270**D - Diameter (mm):** Ø50**Net Weight (kg):** 0.678**MATERIALS****Body Material:** Polycarbonate tube**Finishing:** Epoxy polyester powder coated**Colour:** Black (B)**Glow-wire Resistance (°C):** 960**OPTICAL SYSTEM****Optical System:** TOP - Opal diffuser**Light Distribution:** Direct**Beam Angle (°):** 124**TECHNICAL DATA****Light Source:** LED**Input Power (W):** 23**Power Factor (λ):** 1**NOTES**

- To complete the product it is necessary to order the current supply cable and the ceiling rose. Please order separately.