


## TTP 50 360 VRT L1270 TOP 830 B

TUBULAR LUMINAIRES

90555L1200B0300



### Light distribution



### PRODUCT DESCRIPTION

**Application Areas:** Public spaces, Industry, Outside

**Mounting Type:** Suspended

**Control Gear Included:** No

## TTP 50 360 VRT L1270 TOP 830 B

### CHARACTERISTICS

**Luminaire Type:** Straight line luminaire

**Luminaire Module:** Individual

**Insulation Class:** III

**Ingress Protection (IP):** 40

**Ambient Temperature Range (°C):** ]-10, 25[

**Warranty (Years):** 5

**Current Supply Cable Entry Point:** End cap

**Luminaire Luminous Flux (lm):** 2583

**Luminaire Efficacy (lm/W):** 112

**Unified Glare Rating (UGR):** <22

**LED Lifetime - Rated Median Useful Life:** 70.000h @ L80, B10, Ta 25°C

**CCT - Correlated Colour Temperature (K):** 3000

**Colour Rendering Index (CRI):** >80

**Chromaticity Tolerance (MacAdam step):** <3

**This Product Contains a Light Source of Energy Efficiency Class:** D

**LED Module Forward Voltage Range (VF):** 21,5-26,4

**Input luminaire current (mA):** 940

### DIMENSIONS

**L - Length (mm):** 1270

**D - Diameter (mm):** Ø50

**Net Weight (kg):** 0.678

### MATERIALS

**Body Material:** Polycarbonate tube

**Finishing:** Epoxy polyester powder coated

**Colour:** Black (B)

**Glow-wire Resistance (°C):** 960

### OPTICAL SYSTEM

**Optical System:** TOP - Opal diffuser

**Light Distribution:** Direct

**Beam Angle (°):** 124

### TECHNICAL DATA

**Light Source:** LED

**Input Power (W):** 23

**Power Factor (λ):** 1

### NOTES

- To complete the product it is necessary to order the current supply cable and the ceiling rose. Please order separately.