



## ROFY 60 D/I D1150 GCONTROL+ HF K3 830 7 LO

ARCHITECTURAL LIGHTING

90588L115E73300



### Light distribution



### PRODUCT DESCRIPTION

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

**Mounting Type:** Surface mounted, Suspended, Wall mounted

**Control Gear Included:** Yes

**Control Gear:** LED driver 220-240VAC-50/60Hz

## ROFY 60 D/I D1150 GCONTROL+ HF K3 830 7 LO

### CHARACTERISTICS

**Luminaire Type:** Circular luminaire

**Luminaire Module:** Individual

**Insulation Class:** I

**Ingress Protection (IP):** 40

**Mechanical Impact Protection (IK):** 04

**Ambient Temperature Range (°C):** ]5, 25[

**Warranty (Years):** 5

**Current Supply Cable Entry Point:** Back

### MATERIALS

**Body Material:** Aluminium

**Frame Material:** Extruded aluminium profile

**Finishing:** Epoxy polyester powder coated

**Colour:** Cooper (7)

**Glow-wire Resistance (°C):** 650

### OPTICAL SYSTEM

**Optical System:** GCONTROL+ - Difusor microprismático

**Light Distribution:** Direct / Indirect

**Beam Angle (°):** 94

### TECHNICAL DATA

**Light Source:** LED

**Input Power (W):** 114

**Input Driver Voltage:** 220-240V-50/60Hz

**Power Factor (λ):** 0,96

**Luminaire Luminous Flux (lm):** 14777

**Luminaire Efficacy (lm/W):** 130

**Emergency Unit:** 3

**Unified Glare Rating (UGR):** <16

**LED Lifetime - Rated Median Useful Life:** 80.000h @ L90, B10, Ta 25°C

**CCT - Correlated Colour Temperature (K):** 3000

**Colour Rendering Index (CRI):** >80

**Chromaticity Tolerance (MacAdam step):** <3

**This Product Contains a Light Source of Energy Efficiency Class:** B

**LED Module Forward Voltage Range (VF):** 191,6 + 120,8

**Power Supply Dimming:** ON/OFF

**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <8

**Inrush Current (A):** <8

**Pulse Duration (μs):** <8

**This Product contains a Light Source of Energy Efficiency Class**

**[Indirect]:** C

### DIMENSIONS

**H - Height (mm):** 85

**D - Diameter (mm):** 1150

### NOTES

- For suspended version it is necessary to order the suspension, the current supply cable and the ceiling rose. Please order separately;
- In order to guarantee total light uniformity on the ceiling in the suspended version, installation must be carried out at a minimum distance of 500 mm.