


ROFY 85 /E D0400 LIGHT+ DALI 840 R HO

ARCHITECTURAL LIGHTING

90621L400HR0000



Light distribution



PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

Mounting Type: Recessed

Control Gear Included: Yes

Control Gear: LED driver 220-240VAC-50/60Hz

ROFY 85 /E D0400 LIGHT+ DALI 840 R HO

CHARACTERISTICS

Luminaire Type: Circular luminaire

Luminaire Module: Individual

Insulation Class: II

Ingress Protection (IP): 20

Mechanical Impact Protection (IK): 04

Ambient Temperature Range (°C):]-5, 25[

Fixing System: Brackets

Ceiling Thickness (mm): 1-25

Warranty (Years): 5

Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Steel sheet

Frame Material: Extruded aluminium profile

Finishing: Epoxy polyester powder coated

Colour: Rusty chain (R)

Glow-wire Resistance (°C): 650

OPTICAL SYSTEM

Optical System: LIGHT+ - Opal diffuser

Light Distribution: Direct

Beam Angle (°): 106

TECHNICAL DATA

Light Source: LED

Input Power (W): 26

Input Driver Voltage: 220-240V-50/60Hz

Power Factor (λ): 0,97

Luminaire Luminous Flux (lm): 3385

Luminaire Efficacy (lm/W): 130

Unified Glare Rating (UGR): <25

LED Lifetime - Rated Median Useful Life: 80.000h @ L90, B10, Ta 25°C

CCT - Correlated Colour Temperature (K): 4000

Colour Rendering Index (CRI): >80

Chromaticity Tolerance (MacAdam step): <3

This Product Contains a Light Source of Energy Efficiency Class: C

LED Module Forward Voltage Range (VF): 26,8

Power Supply Dimming: DALI 2

Central Battery Emergency Lighting System (VDC): 198-280

Maximum of Luminaires by Magnetic Circuit Breaker B16: <25

Inrush Current (A): 5

Pulse Duration (µs): 45

DIMENSIONS

H - Height (mm): 85

D - Diameter (mm): 400

D - Recess Dimensions (mm): 377-386

H - Recess Height (mm): 115

NOTES

- This product cannot be wall applied.