

## ROFY 85 D/I D1150 LIGHT+ DALI 830 1 HO

90623L115H10300

ARCHITECTURAL LIGHTING



## Light distribution



## PRODUCT DESCRIPTION

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

**Mounting Type:** Suspended

**Control Gear Included:** Yes

**Control Gear:** LED driver 220-240VAC-50/60Hz

## ROFY 85 D/I D1150 LIGHT+ DALI 830 1 HO

## CHARACTERISTICS

**Luminaire Type:** Circular luminaire

**Luminaire Module:** Individual

**Insulation Class:** I

**Ingress Protection (IP):** 40

**Mechanical Impact Protection (IK):** 04

**Ambient Temperature Range (°C):** ]-5, 25[

**Warranty (Years):** 5

**Current Supply Cable Entry Point:** Back

## MATERIALS

**Body Material:** Steel sheet

**Frame Material:** Extruded aluminium profile

**Finishing:** Epoxy polyester powder coated

**Colour:** Mist (1)

**Glow-wire Resistance (°C):** 650

## OPTICAL SYSTEM

**Optical System:** LIGHT+ - Opal diffuser

**Light Distribution:** Direct / Indirect

**Beam Angle (°):** 106

## TECHNICAL DATA

**Light Source:** LED

**Input Power (W):** 144

**Input Driver Voltage:** 220-240V-50/60Hz

**Power Factor (λ):** 0,97

**Luminaire Luminous Flux (lm):** 18523

**Luminaire Efficacy (lm/W):** 129

**Unified Glare Rating (UGR):** <22

**LED Lifetime - Rated Median Useful Life:** 80.000h @ L90, B10, Ta 25°C

**CCT - Correlated Colour Temperature (K):** 3000

**Colour Rendering Index (CRI):** >80

**Chromaticity Tolerance (MacAdam step):** <3

**This Product Contains a Light Source of Energy Efficiency Class:** B

**LED Module Forward Voltage Range (VF):** 199,2 + 123,2

**Power Supply Dimming:** DALI 2

**Central Battery Emergency Lighting System (VDC):** 176-280

**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <12

**Inrush Current (A):** 37

**Pulse Duration (μs):** 147

**This Product contains a Light Source of Energy Efficiency Class**

**[Indirect]:** C

## DIMENSIONS

**H - Height (mm):** 85

**D - Diameter (mm):** 1150

## NOTES

- To complete the product it is necessary to order the suspension, the current supply cable and ceiling rose. Please order separately;
- In order to guarantee a total uniformity of light on the ceiling, the installation must be done at a minimum distance of 500 mm.