


ELI /W L150 PB HF 940 W 35° HO

ARCHITECTURAL LIGHTING

90646L150EW0035**Light distribution****PRODUCT DESCRIPTION****Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care**Mounting Type:** Wall mounted**Control Gear Included:** Yes**Control Gear:** LED driver 220-240VAC-50/60Hz**ELI /W L150 PB HF 940 W 35° HO****CHARACTERISTICS****Luminaire Type:** Round downlight**Insulation Class:** I**Ingress Protection (IP):** 20**Ambient Temperature Range (°C):**]-5, 25[**Warranty (Years):** 5**Current Supply Cable Entry Point:** Side**MATERIALS****Body Material:** Extruded aluminium profile**Finishing:** Epoxy polyester powder coated**Colour:** White (W)**Glow-wire Resistance (°C):** 650**OPTICAL SYSTEM****Optical System:** Narrow - narrow beam angle**Light Distribution:** Direct**Beam Angle (°):** 27°**TECHNICAL DATA****Light Source:** LED**Input Power (W):** 9**Input Driver Voltage:** 220-240V-50/60Hz**Power Factor (λ):** 0,87**Luminaire Luminous Flux (lm):** 1161**Luminaire Efficacy (lm/W):** 129**Unified Glare Rating (UGR):** <16**LED Lifetime - Rated Median Useful Life:** 66.000h @ L90, B10, Ta 25°C**CCT - Correlated Colour Temperature (K):** 4000**Photobiological safety according to IEC 62471:** Not Available**Colour Rendering Index (CRI):** >90**Chromaticity Tolerance (MacAdam step):** <3**This Product Contains a Light Source of Energy Efficiency Class:** E**LED Module Forward Voltage Range (VF):** 32,65**Power Supply Dimming:** ON/OFF**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <85**Inrush Current (A):** 9**Pulse Duration (µs):** 140**DIMENSIONS****H - Height (mm):** 150**D - Diameter (mm):** 80**Net Weight (kg):** 0.69