

ELI /E 1 PB 930 W 60° LO

ARCHITECTURAL LIGHTING

90661L0010W0360**Light distribution****PRODUCT DESCRIPTION**

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

Mounting Type: Recessed

Control Gear Included: No

ELI /E 1 PB 930 W 60° LO**CHARACTERISTICS**

Luminaire Type: Round downlight

Insulation Class: III

Ingress Protection (IP): 20

Ambient Temperature Range (°C):]-5, 25[

Ceiling Thickness (mm): 1-25

Warranty (Years): 5

MATERIALS

Body Material: Extruded aluminium profile

Finishing: Epoxy polyester powder coated

Colour: White (W)

Glow-wire Resistance (°C): 650

OPTICAL SYSTEM

Optical System: Medium - medium beam angle

Light Distribution: Direct

Beam Angle (°): 53°

TECHNICAL DATA

Light Source: LED

Input Power (W): 5

Power Factor (λ): 1

Luminaire Luminous Flux (lm): 655

Luminaire Efficacy (lm/W): 131

Unified Glare Rating (UGR): <19

LED Lifetime - Rated Median Useful Life: 66.000h @ L90, B10, Ta 25°C

CCT - Correlated Colour Temperature (K): 3000

Photobiological safety according to IEC 62471: Not Available

Colour Rendering Index (CRI): >90

Chromaticity Tolerance (MacAdam step): <3

This Product Contains a Light Source of Energy Efficiency Class: E

LED Module Forward Voltage Range (VF): 32,2

Input luminaire current (mA): 150

DIMENSIONS

H - Height (mm): 106.5

D - Diameter (mm): 115

D - Recess Dimensions (mm): 95-100

H - Recess Height (mm): 95

Net Weight (kg): 0.5

NOTES

- To complete the product it is necessary to order the driver separately.