



ELI SQ /E 2 PB 930 W 35° LO

ARCHITECTURAL LIGHTING

90673L0020W0335



Light distribution



L=215mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

Mounting Type: Recessed

Control Gear Included: No

ELI SQ /E 2 PB 930 W 35° LO

CHARACTERISTICS

Luminaire Type: Double downlight

Insulation Class: III

Ingress Protection (IP): 20

Ambient Temperature Range (°C):]-5, 25[

Ceiling Thickness (mm): 1-25

Warranty (Years): 5

MATERIALS

Body Material: Extruded aluminium profile

Finishing: Epoxy polyester powder coated

Colour: White (W)

Glow-wire Resistance (°C): 650

OPTICAL SYSTEM

Optical System: Narrow - narrow beam angle

Light Distribution: Direct

Beam Angle (°): 27°

TECHNICAL DATA

Light Source: LED

Input Power (W): 10

Power Factor (λ): 1

Luminaire Luminous Flux (lm): 1326

Luminaire Efficacy (lm/W): 133

Unified Glare Rating (UGR): <16

LED Lifetime - Rated Median Useful Life: 66.000h @ L90, B10, Ta 25°C

CCT - Correlated Colour Temperature (K): 3000

Photobiological safety according to IEC 62471: Not Available

Colour Rendering Index (CRI): >90

Chromaticity Tolerance (MacAdam step): <3

This Product Contains a Light Source of Energy Efficiency Class: E

LED Module Forward Voltage Range (VF): 32,2

Input luminaire current (mA): 300

DIMENSIONS

L - Length (mm): 215

W - Width (mm): 115

H - Height (mm): 96.5

D - Recess Dimensions (mm): 105

H - Recess Height (mm): 105

Net Weight (kg): 1.1

NOTES

- To complete the product it is necessary to order the driver separately.