



TTP 50 360 HRZ L1570 TOP 840 G

TUBULAR LUMINAIRES

90677L1500G0000



Light distribution



L=1572mm

PRODUCT DESCRIPTION

Application Areas: Public spaces, Industry, Outside

Mounting Type: Suspended

Control Gear Included: No

TTP 50 360 HRZ L1570 TOP 840 G

CHARACTERISTICS

Luminaire Type: Straight line luminaire

Luminaire Module: Individual

Insulation Class: III

Ingress Protection (IP): 40

Ambient Temperature Range (°C):]-10, 25[

Fixing System: Clamp

Warranty (Years): 5

Current Supply Cable Entry Point: Tube

Power Factor (λ): 1

Luminaire Luminous Flux (lm): 3356

Luminaire Efficacy (lm/W): 120

Unified Glare Rating (UGR): <22

LED Lifetime - Rated Median Useful Life: 70.000h @ L80, B10, Ta 25°C

CCT - Correlated Colour Temperature (K): 4000

Colour Rendering Index (CRI): >80

Chromaticity Tolerance (MacAdam step): <3

This Product Contains a Light Source of Energy Efficiency Class: D

LED Module Forward Voltage Range (VF): 21,5-26,4

Input luminaire current (mA): 1175

DIMENSIONS

L - Length (mm): 1572

D - Diameter (mm): Ø50

Net Weight (kg): 0.85

MATERIALS

Body Material: Polycarbonate tube

Finishing: Epoxy polyester powder coated

Colour: Grey (G)

Glow-wire Resistance (°C): 960

OPTICAL SYSTEM

Optical System: TOP - Opal diffuser

Light Distribution: Direct

Beam Angle (°): 124

TECHNICAL DATA

Light Source: LED

Input Power (W): 28

NOTES

- To complete the product it is necessary to order the suspension, the current supply cable and ceiling rose. Please order separately.