




## ELI 50 SQ /W L200 PB DALI 930 W 20° LO

ARCHITECTURAL LIGHTING

90691L200HW0320



### Light distribution



L=50mm

### PRODUCT DESCRIPTION

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

**Mounting Type:** Wall mounted

**Control Gear Included:** Yes

**Control Gear:** LED driver 220-240VAC-50/60Hz

## ELI 50 SQ /W L200 PB DALI 930 W 20° LO

### CHARACTERISTICS

**Luminaire Type:** Square downlight

**Insulation Class:** I

**Ingress Protection (IP):** 20

**Ambient Temperature Range (°C):** ]-5, 25[

**Warranty (Years):** 5

**Current Supply Cable Entry Point:** Side

### MATERIALS

**Body Material:** Extruded aluminium profile

**Finishing:** Epoxy polyester powder coated

**Colour:** White (W)

**Glow-wire Resistance (°C):** 850

### OPTICAL SYSTEM

**Optical System:** PB - Shiny reflector

**Light Distribution:** Direct

**Beam Angle (°):** 20°

### TECHNICAL DATA

**Light Source:** LED

**Input Power (W):** 7

**Input Driver Voltage:** 220-240V-50/60Hz

**Power Factor (λ):** 0,93

**Luminaire Luminous Flux (lm):** 712

**Luminaire Efficacy (lm/W):** 102

**Unified Glare Rating (UGR):** <19

**LED Lifetime - Rated Median Useful Life:** 60.000h @ L80, B10, Ta 25°C

**CCT - Correlated Colour Temperature (K):** 3000

**Colour Rendering Index (CRI):** >90

**Chromaticity Tolerance (MacAdam step):** <3

**This Product Contains a Light Source of Energy Efficiency Class:** E

**LED Module Forward Voltage Range (VF):** 33,4

**Power Supply Dimming:** DALI 2

**Central Battery Emergency Lighting System (VDC):** 176-276

**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <100

**Inrush Current (A):** 5

**Pulse Duration (µs):** 100

### DIMENSIONS

**L - Length (mm):** 50

**W - Width (mm):** 75

**H - Height (mm):** 200