


ELI 50 SPOT /E 2 PB 930 W 50° HO

ARCHITECTURAL LIGHTING

90702L0020W0350



Light distribution



L=65mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

Mounting Type: Recessed

Control Gear Included: No

ELI 50 SPOT /E 2 PB 930 W 50° HO

CHARACTERISTICS

Luminaire Type: Double downlight

Insulation Class: III

Ingress Protection (IP): 20

Ambient Temperature Range (°C):]-5, 25[

Ceiling Thickness (mm): 1-25

Warranty (Years): 5

MATERIALS

Body Material: Extruded aluminium profile

Finishing: Epoxy polyester powder coated

Colour: White (W)

Glow-wire Resistance (°C): 850

OPTICAL SYSTEM

Optical System: PB - Shiny reflector

Light Distribution: Direct

Beam Angle (°): 50°

Adjustable: Tilt / Rotation

TECHNICAL DATA

Light Source: LED

Input Power (W): 17

Power Factor (λ): 1

Luminaire Luminous Flux (lm): 2177

Luminaire Efficacy (lm/W): 128

Unified Glare Rating (UGR): <22

LED Lifetime - Rated Median Useful Life: 60.000h @ L80, B10, Ta 25°C

CCT - Correlated Colour Temperature (K): 3000

Colour Rendering Index (CRI): >90

Chromaticity Tolerance (MacAdam step): <3

This Product Contains a Light Source of Energy Efficiency Class: E

LED Module Forward Voltage Range (VF): 34,9

Input luminaire current (mA): 500

DIMENSIONS

L - Length (mm): 65

W - Width (mm): 125

D - Recess Dimensions (mm): 45-50 / 105-110

H - Recess Height (mm): 32

NOTES

• To complete the product it is necessary to order the driver separately.