



ROFY 60 SQ L1342W286 LIGHT+ DALI 8TW 1
 ARCHITECTURAL LIGHTING

90720L132H10T00

**Light distribution**

L=1342mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

Mounting Type: Surface mounted, Suspended, Wall mounted

Control Gear Included: Yes

Control Gear: LED driver 220-240VAC-50/60Hz

ROFY 60 SQ L1342W286 LIGHT+ DALI 8TW 1**CHARACTERISTICS**

Luminaire Type: Rectangular luminaire

Luminaire Module: Individual

Insulation Class: I

Ingress Protection (IP): 40

Mechanical Impact Protection (IK): 04

Ambient Temperature Range (°C):]-5, 25[

Warranty (Years): 5

Current Supply Cable Entry Point: Back

Light Source: LED

Input Power (W): 57

Input Driver Voltage: 220-240V-50/60Hz

Power Factor (λ): 0,96

LED Lifetime - Rated Median Useful Life: 80.000h @ L90, B10, Ta 25°C

CCT - Correlated Colour Temperature (K): 2700-6500

Colour Rendering Index (CRI): >80

Chromaticity Tolerance (MacAdam step): <3

LED Module Forward Voltage Range (VF): 150

Power Supply Dimming: DALI 2

Central Battery Emergency Lighting System (VDC): 176-276

Maximum of Luminaires by Magnetic Circuit Breaker B16: <20

Inrush Current (A): 23

DIMENSIONS

L - Length (mm): 1342

W - Width (mm): 286

H - Height (mm): 85

MATERIALS

Body Material: Aluminium

Frame Material: Extruded aluminium profile

Finishing: Epoxy polyester powder coated

Colour: Mist (1)

Glow-wire Resistance (°C): 650

OPTICAL SYSTEM

Optical System: LIGHT+ - Opal diffuser

Light Distribution: Direct

TECHNICAL DATA**NOTES**

- For suspended version it is necessary to order the suspension, the current supply cable and the ceiling rose. Please order separately.