

**CORA /C L15W30 2 BOPTICS DALI 840 B LO**

TECHNICAL LIGHTING

**90725L215HB0000****Light distribution**

L=1497mm

**PRODUCT DESCRIPTION****Application Areas:** Offices, Education, Health and care**Mounting Type:** Surface mounted**Control Gear Included:** Yes**Control Gear:** LED driver 220-240VAC-50/60Hz**CORA /C L15W30 2 BOPTICS DALI 840 B LO****CHARACTERISTICS****Luminaire Type:** Rectangular luminaire**Luminaire Module:** Individual**Insulation Class:** I**Ingress Protection (IP):** 20**Ambient Temperature Range (°C):** ]-5, 25[**Warranty (Years):** 5**Current Supply Cable Entry Point:** Back**MATERIALS****Body Material:** Steel sheet**Finishing:** Epoxy polyester powder coated**Colour:** Black (B)**Glow-wire Resistance (°C):** 650**OPTICAL SYSTEM****Optical System:** bOPTICS - Symmetric reflector**Light Distribution:** Direct**Beam Angle (°):** 44**TECHNICAL DATA****Light Source:** LED**Input Power (W):** 36**Input Driver Voltage:** 220-240V-50/60Hz**Power Factor (λ):** 0,96**Luminaire Luminous Flux (lm):** 4709**Luminaire Efficacy (lm/W):** 131**Unified Glare Rating (UGR):** <10**LED Lifetime - Rated Median Useful Life:** 80.000h @ L90, B10, Ta 25°C**CCT - Correlated Colour Temperature (K):** 4000**Colour Rendering Index (CRI):** >80**Chromaticity Tolerance (MacAdam step):** <3**LED Module Forward Voltage Range (VF):** 32,6**Power Supply Dimming:** DALI 2**Maximum of luminaires by Magnetic Circuit Breaker B16:** <34**Inrush Current (A):** 18**Pulse Duration (μs):** 180**DIMENSIONS****L - Length (mm):** 1497**W - Width (mm):** 297**H - Height (mm):** 30**Net Weight (kg):** 5.8