


CORA /C L60W60 3 BOPTICS DALI K3 840 W HO

90728Q360HW3000

TECHNICAL LIGHTING



Light distribution



L=597mm

PRODUCT DESCRIPTION

Application Areas: Offices, Education, Health and care**Mounting Type:** Surface mounted**Control Gear Included:** Yes**Control Gear:** LED driver 220-240VAC-50/60Hz

CORA /C L60W60 3 BOPTICS DALI K3 840 W HO

CHARACTERISTICS

Luminaire Type: Square luminaire**Luminaire Module:** Individual**Insulation Class:** I**Ingress Protection (IP):** 20**Ambient Temperature Range (°C):**]5, 25[**Warranty (Years):** 5**Current Supply Cable Entry Point:** Back

MATERIALS

Body Material: Steel sheet**Finishing:** Epoxy polyester powder coated**Colour:** White (W)**Glow-wire Resistance (°C):** 650

OPTICAL SYSTEM

Optical System: bOPTICS - Symmetric reflector**Light Distribution:** Direct**Beam Angle (°):** 44

TECHNICAL DATA

Light Source: LED**Input Power (W):** 26**Input Driver Voltage:** 220-240V-50/60Hz**Power Factor (λ):** 0,94**Luminaire Luminous Flux (lm):** 3408**Luminaire Efficacy (lm/W):** 131**Emergency Unit:** 3**Unified Glare Rating (UGR):** <10**LED Lifetime - Rated Median Useful Life:** 80.000h @ L90, B10, Ta 25°C**CCT - Correlated Colour Temperature (K):** 4000**Colour Rendering Index (CRI):** >80**Chromaticity Tolerance (MacAdam step):** <3**LED Module Forward Voltage Range (VF):** 33,7**Power Supply Dimming:** DALI 2**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <50**Inrush Current (A):** 21**Pulse Duration (μ s):** 115

DIMENSIONS

L - Length (mm): 597**W - Width (mm):** 597**H - Height (mm):** 30**Net Weight (kg):** 4.9