

# CORA /E L15W30 2 BOPTICS DALI K3 830 W HO

90729L215HW3300

TECHNICAL LIGHTING



## Light distribution



L=1497mm

## PRODUCT DESCRIPTION

**Application Areas:** Offices, Education, Health and care

**Mounting Type:** Recessed

**Control Gear Included:** Yes

**Control Gear:** LED driver 220-240VAC-50/60Hz

## CORA /E L15W30 2 BOPTICS DALI K3 830 W HO

## CHARACTERISTICS

**Luminaire Type:** Rectangular luminaire

**Luminaire Module:** Individual

**Insulation Class:** II

**Ingress Protection (IP):** 20

**Ambient Temperature Range (°C):** ]5, 25[

**Ceiling Thickness (mm):** 1-25

**Warranty (Years):** 5

**Current Supply Cable Entry Point:** Back

## MATERIALS

**Body Material:** Steel sheet

**Finishing:** Epoxy polyester powder coated

**Colour:** White (W)

**Glow-wire Resistance (°C):** 650

## OPTICAL SYSTEM

**Optical System:** bOPTICS - Symmetric reflector

**Light Distribution:** Direct

**Beam Angle (°):** 44

## TECHNICAL DATA

**Light Source:** LED

**Input Power (W):** 55

**Input Driver Voltage:** 220-240V-50/60Hz

**Power Factor (λ):** 0,98

**Luminaire Luminous Flux (lm):** 6552

**Luminaire Efficacy (lm/W):** 119

**Emergency Unit:** 3

**Unified Glare Rating (UGR):** <10

**LED Lifetime - Rated Median Useful Life:** 80.000h @ L90, B10, Ta 25°C

**CCT - Correlated Colour Temperature (K):** 3000

**Colour Rendering Index (CRI):** >80

**Chromaticity Tolerance (MacAdam step):** <3

**LED Module Forward Voltage Range (VF):** 33,7

**Power Supply Dimming:** DALI 2

**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <40

**Inrush Current (A):** 19

**Pulse Duration (µs):** 115

## DIMENSIONS

**L - Length (mm):** 1497

**W - Width (mm):** 297

**H - Height (mm):** 27.2

**D - Recess Dimensions (mm):** 1472x272

**H - Recess Height (mm):** 79

**Net Weight (kg):** 4.3

## NOTES

- For the recessed version in plasterboard ceilings order the recessed mounting kit (x4). Please order separately.