



## REBA 50 BOPTICS INT L0638 SYM BOPTICS DALI 830 B HO

90747L002HB0300

ALUMINIUM PROFILE SYSTEMS



## Light distribution



L=637mm

## PRODUCT DESCRIPTION

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

**Mounting Type:** Surface mounted, Suspended

**Control Gear Included:** No

## REBA 50 BOPTICS INT L0638 SYM BOPTICS DALI 830 B HO

## CHARACTERISTICS

**Luminaire Type:** Straight line luminaire

**Luminaire Module:** Individual

**Insulation Class:** I

**Ingress Protection (IP):** 40

**Ambient Temperature Range (°C):** ]-5, 25[

**Warranty (Years):** 5

**Current Supply Cable Entry Point:** Back

## MATERIALS

**Body Material:** Extruded aluminium profile

**Finishing:** Epoxy polyester powder coated

**Colour:** Black (B)

**Glow-wire Resistance (°C):** 650

## OPTICAL SYSTEM

**Optical System:** bOPTICS - Symmetric reflector

**Light Distribution:** Direct

**Beam Angle (°):** 45

## TECHNICAL DATA

**Light Source:** LED

**Input Power (W):** 13

**Input Driver Voltage:** 220-240V-50/60Hz

**Power Factor (λ):** 0,88

**Luminaire Luminous Flux (lm):** 1422

**Luminaire Efficacy (lm/W):** 109

**Unified Glare Rating (UGR):** <10

**LED Lifetime - Rated Median Useful Life:** 80.000h @ L90, B10, Ta 25°C

**CCT - Correlated Colour Temperature (K):** 3000

**Colour Rendering Index (CRI):** >80

**Chromaticity Tolerance (MacAdam step):** <3

**LED Module Forward Voltage Range (VF):** 33,7

**Power Supply Dimming:** DALI 2

**Central Battery Emergency Lighting System (VDC):** 176-280

**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <50

**Inrush Current (A):** 21

**Pulse Duration (μs):** 115

## DIMENSIONS

**L - Length (mm):** 637

**W - Width (mm):** 46.5

**H - Height (mm):** 66.5

## NOTES

- To complete the product it is necessary to order the inner profile separately;
- For suspended version it is necessary to order the suspension, the current supply cable and the ceiling rose. Please order separately.