



**DYNA /C D236 PM HF 830 W 80° LO**

ARCHITECTURAL LIGHTING

**90759L00LEW0300****Light distribution****PRODUCT DESCRIPTION**

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

**Mounting Type:** Surface mounted

**Control Gear Included:** Yes

**Control Gear:** LED driver 220-240VAC-50/60Hz

**DYNA /C D236 PM HF 830 W 80° LO****CHARACTERISTICS**

**Luminaire Type:** Round downlight

**Luminaire Module:** Individual

**Insulation Class:** I

**Ingress Protection (IP):** 20

**Ambient Temperature Range (°C):** ]-5, 25[

**Warranty (Years):** 5

**Current Supply Cable Entry Point:** Back

**MATERIALS**

**Body Material:** Aluminium

**Finishing:** Epoxy polyester powder coated

**Colour:** White (W)

**Glow-wire Resistance (°C):** 650

**OPTICAL SYSTEM**

**Optical System:** PM - Matte reflector

**Light Distribution:** Direct

**Beam Angle (°):** 84

**TECHNICAL DATA**

**Light Source:** LED

**Input Power (W):** 9

**Input Driver Voltage:** 220-240V-50/60Hz

**Power Factor (λ):** 0,83

**Luminaire Luminous Flux (lm):** 1087

**Luminaire Efficacy (lm/W):** 121

**Unified Glare Rating (UGR):** <16

**LED Lifetime - Rated Median Useful Life:** 60.000h @ L70, B10, Ta 25°C

**CCT - Correlated Colour Temperature (K):** 3000

**Colour Rendering Index (CRI):** >80

**Chromaticity Tolerance (MacAdam step):** <3

**This Product Contains a Light Source of Energy Efficiency Class:** E

**LED Module Forward Voltage Range (VF):** 32,4

**Power Supply Dimming:** ON/OFF

**Central Battery Emergency Lighting System (VDC):** 176-280

**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <30

**Inrush Current (A):** 15

**Pulse Duration (µs):** 100

**DIMENSIONS**

**H - Height (mm):** 170

**D - Diameter (mm):** 242

**Net Weight (kg):** 2.5