



## AURA L600 LIGHT+ HF 830 B

ARCHITECTURAL LIGHTING

90825L060EB0300



### Light distribution



L=600mm

### PRODUCT DESCRIPTION

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

**Mounting Type:** Wall mounted

**Control Gear Included:** Yes

**Control Gear:** LED driver 220-240VAC-50/60Hz

**Power Factor ( $\lambda$ ):** 0,95

**Luminaire Luminous Flux (lm):** 3866

**Luminaire Efficacy (lm/W):** 125

**LED Lifetime - Rated Median Useful Life [Indirect]:** 80.000h @ L80, B10, Ta 25°C

**CCT - Correlated Colour Temperature (K) [Indirect]:** 3000

**Colour Rendering Index (CRI) [Indirect]:** >80

**Chromaticity Tolerance (MacAdam step) [Indirect]:** <3

**This Product contains a Light Source of Energy Efficiency Class [Indirect]:** C

**Power Supply Dimming [Indirect]:** ON/OFF

## AURA L600 LIGHT+ HF 830 B

### CHARACTERISTICS

**Luminaire Type:** Rectangular luminaire

**Luminaire Module:** Individual

**Insulation Class:** I

**Ingress Protection (IP):** 40

**Ambient Temperature Range (°C):** ]-5, 25[

**Warranty (Years):** 5

**Current Supply Cable Entry Point:** Back

### DIMENSIONS

**L - Length (mm):** 600

**W - Width (mm):** 100

**H - Height (mm):** 45

### MATERIALS

**Body Material:** Steel sheet

**Finishing:** Epoxy polyester powder coated

**Colour:** Black (B)

**Glow-wire Resistance (°C):** 650

### OPTICAL SYSTEM

**Optical System:** LIGHT+ - Opal diffuser

**Light Distribution:** Indirect

**Beam Angle (°):** 111

### TECHNICAL DATA

**Input Power (W):** 31