



AVL L1121 DPT HF K3 840 W

BATTENS AND TRACK SYSTEMS

90826L120EW3000**Light distribution**

L=561mm

PRODUCT DESCRIPTION**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care**Mounting Type:** Surface mounted**Control Gear Included:** Yes**Control Gear:** LED driver 220-240VAC-50/60Hz**AVL L1121 DPT HF K3 840 W****CHARACTERISTICS****Luminaire Type:** Rectangular luminaire**Luminaire Module:** Individual, Start (SRT), Middle (MID), End (END)**Insulation Class:** I**Ingress Protection (IP):** 20**Ambient Temperature Range (°C):**]5, 25[**Warranty (Years):** 5**Current Supply Cable Entry Point:** Back**MATERIALS****Body Material:** Steel sheet**Finishing:** Epoxy polyester powder coated**Colour:** White (W)**Glow-wire Resistance (°C):** 650**OPTICAL SYSTEM****Optical System:** DPT - Transparent diffuser**Light Distribution:** Direct**Beam Angle (°):** 113**TECHNICAL DATA****Light Source:** LED**Input Power (W):** 24**Input Driver Voltage:** 220-240V-50/60Hz**Power Factor (λ):** 0,95**Luminaire Luminous Flux (lm):** 3571**Luminaire Efficacy (lm/W):** 149**Emergency Unit:** 3**Unified Glare Rating (UGR):** <25**LED Lifetime - Rated Median Useful Life:** 80.000h @ L80, B10, Ta 25°C**CCT - Correlated Colour Temperature (K):** 4000**Colour Rendering Index (CRI):** >80**Chromaticity Tolerance (MacAdam step):** <3**This Product Contains a Light Source of Energy Efficiency Class:** C**LED Module Forward Voltage Range (VF):** 32,7**Power Supply Dimming:** ON/OFF**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <34**Inrush Current (A):** 23**Pulse Duration (µs):** 176**DIMENSIONS****L - Length (mm):** 561**W - Width (mm):** 52**H - Height (mm):** 50