



RECESSED CEILING ROSE T52 Q200 21W 10-42V 500MA HF W**972012W**

ARCHITECTURAL LIGHTING



L=200mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

Mounting Type: Suspended

Control Gear Included: No

H - Height (mm): 48

D - Recess Dimensions (mm): 135x135

H - Recess Height (mm): 48

RECESSED CEILING ROSE T52 Q200 21W 10-42V 500MA HF W**CHARACTERISTICS**

Insulation Class: II

Ingress Protection (IP): 20

Ambient Temperature Range (°C):]-5, 25[

Warranty (Years): 5

Current Supply Cable Entry Point: Back

NOTES

- To complete the product it is necessary to order the suspension, the current supply cable and ceiling rose. Please order separately.

MATERIALS

Body Material: Die-cast aluminium

Finishing: Epoxy polyester powder coated

Colour: White (W)

TECHNICAL DATA

Input Power (W): 21

Input Driver Voltage: 220-240V-50/60Hz

Power Supply Dimming: ON/OFF

Maximum of Luminaires by Magnetic Circuit Breaker B16: <30

Inrush Current (A): 15

Pulse Duration (µs): 100

DIMENSIONS

L - Length (mm): 200

W - Width (mm): 200