


RECESSED CEILING ROSE T55 Q200 21W 10-42V 500MA HF R**972712R**

ARCHITECTURAL LIGHTING



L=200mm

PRODUCT DESCRIPTION**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care**Mounting Type:** Suspended**Control Gear Included:** No**H - Height (mm):** 48**D - Recess Dimensions (mm):** 135x135**H - Recess Height (mm):** 48**RECESSED CEILING ROSE T55 Q200 21W 10-42V 500MA HF R****CHARACTERISTICS****Insulation Class:** II**Ingress Protection (IP):** 20**Ambient Temperature Range (°C):**]-5, 25[**Warranty (Years):** 5**Current Supply Cable Entry Point:** Back**NOTES**

- To complete the product it is necessary to order the suspension, the current supply cable and ceiling rose. Please order separately.

MATERIALS**Body Material:** Die-cast aluminium**Finishing:** Epoxy polyester powder coated**Colour:** Rusty chain (R)**TECHNICAL DATA****Input Power (W):** 21**Input Driver Voltage:** 220-240V-50/60Hz**Power Supply Dimming:** ON/OFF**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <30**Inrush Current (A):** 15**Pulse Duration (µs):** 100**DIMENSIONS****L - Length (mm):** 200**W - Width (mm):** 200