


**TRIMLESS RECESSED CEILING ROSE 3I D95 DALI B**  
ARCHITECTURAL LIGHTING**973010B**

IP 20



L=200mm

**PRODUCT DESCRIPTION**

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

**Mounting Type:** Suspended

**Control Gear Included:** No

**NOTES**

- To complete the product it is necessary to order the suspension, the current supply cable and ceiling rose. Please order separately.

**TRIMLESS RECESSED CEILING ROSE 3I D95 DALI B****CHARACTERISTICS**

**Insulation Class:** I

**Ingress Protection (IP):** 20

**Ambient Temperature Range (°C):** ]-5, 25[

**Warranty (Years):** 5

**Current Supply Cable Entry Point:** Back

**MATERIALS**

**Body Material:** Die-cast aluminium

**Finishing:** Epoxy polyester powder coated

**Colour:** Black (B)

**TECHNICAL DATA**

**Input Power (W):** 35,7

**Input Driver Voltage:** 220-240V-50/60Hz

**Power Supply Dimming:** DALI

**DIMENSIONS**

**L - Length (mm):** 200

**W - Width (mm):** 200

**H - Height (mm):** 46

**D - Recess Dimensions (mm):** 135x135

**H - Recess Height (mm):** 46