

**DRIVER 19,8W 03-44V 450MA HF**  
ARCHITECTURAL LIGHTING**900203E**

IP 20

**PRODUCT DESCRIPTION**

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

**Mounting Type:** Recessed

**Control Gear Included:** No

**NOTES**

- To complete the product it is necessary to order the driver separately.

**DRIVER 19,8W 03-44V 450MA HF****CHARACTERISTICS**

**Insulation Class:** II

**Ingress Protection (IP):** 20

**Ambient Temperature Range (°C):** ]-20, 45[

**Ceiling Thickness (mm):** 1-25

**Warranty (Years):** 5

**MATERIALS**

**Body Material:** Aluminium

**Finishing:** Epoxy polyester powder coated

**TECHNICAL DATA**

**Input Power (W):** 19,8

**Input Driver Voltage:** 220-240V-50/60Hz

**Power Supply Dimming:** ON/OFF

**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <25

**Inrush Current (A):** 8

**Pulse Duration (µs):** 48

**DIMENSIONS**

**L - Length (mm):** 97

**W - Width (mm):** 42.5

**H - Height (mm):** 30