




VISA Q110 HF 857 D 90°+ 90° LO
ARCHITECTURAL LIGHTING

90220L101ED0590



Light distribution



L=110mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care
Mounting Type: Wall mounted
Control Gear Included: Yes
Control Gear: LED driver 220-240VAC-50/60Hz

VISA Q110 HF 857 D 90°+ 90° LO

CHARACTERISTICS

Luminaire Type: Square downlight
Luminaire Module: Individual
Insulation Class: I
Ingress Protection (IP): 20
Ambient Temperature Range (°C):]-5, 25[
Warranty (Years): 5
Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Steel sheet
Finishing: Epoxy polyester powder coated
Colour: Golden eye (D)
Glow-wire Resistance (°C): 650

OPTICAL SYSTEM

Light Distribution: Direct / Indirect
Beam Angle (°): 85

TECHNICAL DATA

Light Source: LED
Input Power (W): 3

Input Driver Voltage: 220-240V-50/60Hz
Power Factor (λ): 0,88
Unified Glare Rating (UGR): <13
LED Lifetime - Rated Median Useful Life: 50.000h @ L80, B10, Ta 25°C
CCT - Correlated Colour Temperature (K): 5700
Colour Rendering Index (CRI): >80
Chromaticity Tolerance (MacAdam step): <3
LED Module Forward Voltage Range (VF): 2,9
Power Supply Dimming: ON/OFF
Maximum of Luminaires by Magnetic Circuit Breaker B16: <50
Inrush Current (A): 20
Pulse Duration (µs): 110

DIMENSIONS

L - Length (mm): 110
W - Width (mm): 110
H - Height (mm): 110
Net Weight (kg): 0.7