




HOLI SQ /T Q106 PRISM+ 830 W LO
ARCHITECTURAL LIGHTING

90223L1060W0300



Light distribution



L=106mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care
Mounting Type: Trimless
Control Gear Included: No

HOLI SQ /T Q106 PRISM+ 830 W LO

CHARACTERISTICS

Luminaire Type: Square downlight
Luminaire Module: Individual
Insulation Class: III
Ingress Protection (IP): 40
Ambient Temperature Range (°C):]-5, 25[
Fixing System: Trimless recessed frame
Warranty (Years): 5

MATERIALS

Body Material: Steel sheet
Frame Material: Steel sheet
Finishing: Epoxy polyester powder coated
Colour: White (W)
Glow-wire Resistance (°C): 650

OPTICAL SYSTEM

Optical System: PRISM+ - Microprismatic diffuser
Light Distribution: Direct
Beam Angle (°): 76

TECHNICAL DATA

Light Source: LED

Input Power (W): 7
Power Factor (λ): 1
Luminaire Luminous Flux (lm): 725
Luminaire Efficacy (lm/W): 104
Unified Glare Rating (UGR): <19
LED Lifetime - Rated Median Useful Life: 72.000h @ L70, B10, Ta 25°C
CCT - Correlated Colour Temperature (K): 3000
Colour Rendering Index (CRI): >80
Chromaticity Tolerance (MacAdam step): <3
This Product Contains a Light Source of Energy Efficiency Class: E
LED Module Forward Voltage Range (VF): 33
Input luminaire current (mA): 200

DIMENSIONS

L - Length (mm): 106
W - Width (mm): 106
H - Height (mm): 74
D - Recess Dimensions (mm): 114x114
H - Recess Height (mm): 84
Net Weight (kg): 0.7

NOTES

• To complete the product it is necessary to order the driver and the recessed frame. Please order separately.