



6TH ELEMENT DIR D140 930 W LO 80°
ARCHITECTURAL LIGHTING

90328L0090W0B80



Light distribution



PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care
Mounting Type: Suspended
Control Gear Included: No

6TH ELEMENT DIR D140 930 W LO 80°

CHARACTERISTICS

Luminaire Type: Round downlight
Luminaire Module: Individual
Insulation Class: III
Ingress Protection (IP): 40
Ambient Temperature Range (°C):]-5, 25[
Warranty (Years): 5
Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Die-cast aluminium
Finishing: Epoxy polyester powder coated
Colour: White (W)
Glow-wire Resistance (°C): 650

OPTICAL SYSTEM

Optical System: Lens
Light Distribution: Direct
Beam Angle (°): 78

TECHNICAL DATA

Light Source: LED
Input Power (W): 9

Power Factor (λ): 1

Luminaire Luminous Flux (lm): 1030
Luminaire Efficacy (lm/W): 114
Unified Glare Rating (UGR): <25
LED Lifetime - Rated Median Useful Life: 50.000h @ L80, B10, Ta 25°C
CCT - Correlated Colour Temperature (K): 3000
Colour Rendering Index (CRI): >90
Chromaticity Tolerance (MacAdam step): <3
This Product Contains a Light Source of Energy Efficiency Class: E
LED Module Forward Voltage Range (VF): 34,4
Input luminaire current (mA): 250

DIMENSIONS

H - Height (mm): 80
D - Diameter (mm): 140

NOTES

• To complete the product it is necessary to order the suspension, the current supply cable and ceiling rose. Please order separately.