



**ELI /C L200 PB DALI 940 B 35° LO**  
ARCHITECTURAL LIGHTING

**90347L200HB0035**



**Light distribution**



**PRODUCT DESCRIPTION**

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

**Mounting Type:** Surface mounted

**Control Gear Included:** Yes

**Control Gear:** LED driver 220-240VAC-50/60Hz

**ELI /C L200 PB DALI 940 B 35° LO**

**CHARACTERISTICS**

**Luminaire Type:** Round downlight

**Insulation Class:** I

**Ingress Protection (IP):** 20

**Ambient Temperature Range (°C):** ]-5, 25[

**Warranty (Years):** 5

**Current Supply Cable Entry Point:** Back

**MATERIALS**

**Body Material:** Extruded aluminium profile

**Finishing:** Epoxy polyester powder coated

**Colour:** Black (B)

**Glow-wire Resistance (°C):** 650

**OPTICAL SYSTEM**

**Optical System:** Narrow - narrow beam angle

**Light Distribution:** Direct

**Beam Angle (°):** 27°

**TECHNICAL DATA**

**Light Source:** LED

**Input Power (W):** 6

**Input Driver Voltage:** 220-240V-50/60Hz

**Power Factor (λ):** 0,8

**Luminaire Luminous Flux (lm):** 706

**Luminaire Efficacy (lm/W):** 118

**Unified Glare Rating (UGR):** <13

**LED Lifetime - Rated Median Useful Life:** 66.000h @ L90, B10, Ta 25°C

**CCT - Correlated Colour Temperature (K):** 4000

**Photobiological safety according to IEC 62471:** Not Available

**Colour Rendering Index (CRI):** >90

**Chromaticity Tolerance (MacAdam step):** <3

**This Product Contains a Light Source of Energy Efficiency Class:** E

**LED Module Forward Voltage Range (VF):** 32,2

**Power Supply Dimming:** DALI 2

**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <80

**Inrush Current (A):** 4

**Pulse Duration (µs):** 25

**DIMENSIONS**

**H - Height (mm):** 200

**D - Diameter (mm):** 80

**Net Weight (kg):** 0.705