



**OREO V IN D1955 BLINE 940 L**  
ARCHITECTURAL LIGHTING

90425L1950L0000



**Light distribution**



**PRODUCT DESCRIPTION**

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care  
**Mounting Type:** Suspended  
**Control Gear Included:** No

**OREO V IN D1955 BLINE 940 L**

**CHARACTERISTICS**

**Luminaire Type:** Circular luminaire  
**Insulation Class:** III  
**Ingress Protection (IP):** 40  
**Ambient Temperature Range (°C):** ]-5, 25[  
**Warranty (Years):** 5

**MATERIALS**

**Body Material:** Extruded aluminium profile  
**Finishing:** Epoxy polyester powder coated  
**Colour:** Autumn (L)  
**Glow-wire Resistance (°C):** 850

**OPTICAL SYSTEM**

**Optical System:** bLINE - Opal diffuser  
**Light Distribution:** Direct  
**Beam Angle (°):** 25

**TECHNICAL DATA**

**Light Source:** LED  
**Input Power (W):** 66  
**Power Factor (λ):** 1  
**Luminaire Luminous Flux (lm):** 4203

**Luminaire Efficacy (lm/W):** 64  
**Unified Glare Rating (UGR):** <19  
**LED Lifetime - Rated Median Useful Life:** 60.000h @ L80, B10, Ta 25°C  
**CCT - Correlated Colour Temperature (K):** 4000  
**Photobiological safety according to IEC 62471:** Not Available  
**Colour Rendering Index (CRI):** >90  
**Chromaticity Tolerance (MacAdam step):** <3  
**This Product Contains a Light Source of Energy Efficiency Class:** F  
**LED Module Forward Voltage Range (VF):** 24V DC  
**Input luminaire current (mA):** 2770

**DIMENSIONS**

**H - Height (mm):** 35  
**D - Diameter (mm):** 1955  
**Net Weight (kg):** 6

**NOTES**

- Current supply cable/suspension with 1500 mm included;
- To complete the product it is necessary to order the ceiling rose separately;
- For Ø1540 and Ø1955 mm versions, the product must include a transparent power cable;
- For Tunable White and RGB White versions, the product must include a transparent current supply cable.