



**TALEA GLARE L2558 BLINE K3 840 W**  
TUBULAR LUMINAIRES

90428L1900W3000



**Light distribution**



L=2558mm

**PRODUCT DESCRIPTION**

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care  
**Mounting Type:** Surface mounted, Suspended, Wall mounted  
**Control Gear Included:** No

**TALEA GLARE L2558 BLINE K3 840 W**

**CHARACTERISTICS**

**Luminaire Type:** Straight line luminaire  
**Insulation Class:** III  
**Ingress Protection (IP):** 40  
**Ambient Temperature Range (°C):** ]5, 25[  
**Warranty (Years):** 5  
**Current Supply Cable Entry Point:** Back

**MATERIALS**

**Body Material:** Extruded aluminium profile  
**Finishing:** Epoxy polyester powder coated  
**Colour:** White (W)  
**Glow-wire Resistance (°C):** 960

**OPTICAL SYSTEM**

**Optical System:** bLINE - Opal diffuser  
**Light Distribution:** Direct  
**Beam Angle (°):** 183

**TECHNICAL DATA**

**Light Source:** LED  
**Input Power (W):** 36  
**Power Factor (λ):** 1

**Luminaire Luminous Flux (lm):** 5405  
**Luminaire Efficacy (lm/W):** 150  
**Emergency Unit:** 3  
**Unified Glare Rating (UGR):** <3  
**LED Lifetime - Rated Median Useful Life:** 80.000h @ L90, B10, Ta 25°C  
**CCT - Correlated Colour Temperature (K):** 4000  
**Colour Rendering Index (CRI):** >80  
**Chromaticity Tolerance (MacAdam step):** <3  
**LED Module Forward Voltage Range (VF):** 33,1  
**Input luminaire current (mA):** 1080

**DIMENSIONS**

**L - Length (mm):** 2558  
**D - Diameter (mm):** 100  
**Net Weight (kg):** 7.3

**NOTES**

• To complete the product it is necessary to order the suspension, the current supply cable and ceiling rose. Please order separately.