



TALEA GLARE /C L1438 BLINE DALI 830 W
TUBULAR LUMINAIRES

90429L150HW0300



Light distribution



L=1438mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care
Mounting Type: Surface mounted
Control Gear Included: Yes
Control Gear: LED driver 220-240VAC-50/60Hz

TALEA GLARE /C L1438 BLINE DALI 830 W

CHARACTERISTICS

Luminaire Type: Straight line luminaire
Insulation Class: I
Ingress Protection (IP): 40
Ambient Temperature Range (°C):]-5, 25[
Warranty (Years): 5
Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Extruded aluminium profile
Finishing: Epoxy polyester powder coated
Colour: White (W)
Glow-wire Resistance (°C): 960

OPTICAL SYSTEM

Optical System: bLINE - Opal diffuser
Light Distribution: Direct
Beam Angle (°): 183

TECHNICAL DATA

Light Source: LED
Input Power (W): 19

Input Driver Voltage: 220-240V-50/60Hz
Power Factor (λ): 0,92
Luminaire Luminous Flux (lm): 2772
Luminaire Efficacy (lm/W): 146
Unified Glare Rating (UGR): <19
LED Lifetime - Rated Median Useful Life: 60.000h @ L90, B10, Ta 25°C
CCT - Correlated Colour Temperature (K): 3000
Colour Rendering Index (CRI): >80
Chromaticity Tolerance (MacAdam step): <3
LED Module Forward Voltage Range (VF): 33,1
Power Supply Dimming: DALI 2
Central Battery Emergency Lighting System (VDC): 176-280
Maximum of Luminaires by Magnetic Circuit Breaker B16: <50
Inrush Current (A): 21
Pulse Duration (µs): 115

DIMENSIONS

L - Length (mm): 1438
H - Height (mm): 140
D - Diameter (mm): 100
Net Weight (kg): 5