



TALEA GLARE /C L1718 BLINE HF 840 B
TUBULAR LUMINAIRES

90429L160EB0000



Light distribution



L=1718mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care
Mounting Type: Surface mounted
Control Gear Included: Yes
Control Gear: LED driver 220-240VAC-50/60Hz

TALEA GLARE /C L1718 BLINE HF 840 B

CHARACTERISTICS

Luminaire Type: Straight line luminaire
Insulation Class: I
Ingress Protection (IP): 40
Ambient Temperature Range (°C):]-5, 25[
Warranty (Years): 5
Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Extruded aluminium profile
Finishing: Epoxy polyester powder coated
Colour: Black (B)
Glow-wire Resistance (°C): 960

OPTICAL SYSTEM

Optical System: bLINE - Opal diffuser
Light Distribution: Direct
Beam Angle (°): 183

TECHNICAL DATA

Light Source: LED
Input Power (W): 27

Input Driver Voltage: 220-240V-50/60Hz
Power Factor (λ): 0,94
Luminaire Luminous Flux (lm): 3604
Luminaire Efficacy (lm/W): 133
Unified Glare Rating (UGR): <19
LED Lifetime - Rated Median Useful Life: 60.000h @ L90, B10, Ta 25°C
CCT - Correlated Colour Temperature (K): 4000
Colour Rendering Index (CRI): >80
Chromaticity Tolerance (MacAdam step): <3
LED Module Forward Voltage Range (VF): 33,1
Power Supply Dimming: ON/OFF
Central Battery Emergency Lighting System (VDC): 176-280
Maximum of Luminaires by Magnetic Circuit Breaker B16: <62
Inrush Current (A): 20
Pulse Duration (µs): 161

DIMENSIONS

L - Length (mm): 1718
H - Height (mm): 140
D - Diameter (mm): 100
Net Weight (kg): 5.5