



**TALEA GLARE /C L2278 BLINE DALI K3 840 G**  
TUBULAR LUMINAIRES

90429L180HG3000



**Light distribution**



L=2278mm

**PRODUCT DESCRIPTION**

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care  
**Mounting Type:** Surface mounted  
**Control Gear Included:** Yes  
**Control Gear:** LED driver 220-240VAC-50/60Hz

**TALEA GLARE /C L2278 BLINE DALI K3 840 G**

**CHARACTERISTICS**

**Luminaire Type:** Straight line luminaire  
**Insulation Class:** I  
**Ingress Protection (IP):** 40  
**Ambient Temperature Range (°C):** ]5, 25[  
**Warranty (Years):** 5  
**Current Supply Cable Entry Point:** Back

**MATERIALS**

**Body Material:** Extruded aluminium profile  
**Finishing:** Epoxy polyester powder coated  
**Colour:** Grey (G)  
**Glow-wire Resistance (°C):** 960

**OPTICAL SYSTEM**

**Optical System:** bLINE - Opal diffuser  
**Light Distribution:** Direct  
**Beam Angle (°):** 183

**TECHNICAL DATA**

**Light Source:** LED  
**Input Power (W):** 37

**Input Driver Voltage:** 220-240V-50/60Hz  
**Power Factor (λ):** 0,96  
**Luminaire Luminous Flux (lm):** 4805  
**Luminaire Efficacy (lm/W):** 130  
**Emergency Unit:** 3  
**Unified Glare Rating (UGR):** <19  
**LED Lifetime - Rated Median Useful Life:** 60.000h @ L90, B10, Ta 25°C  
**CCT - Correlated Colour Temperature (K):** 4000  
**Colour Rendering Index (CRI):** >80  
**Chromaticity Tolerance (MacAdam step):** <3  
**LED Module Forward Voltage Range (VF):** 33,1  
**Power Supply Dimming:** DALI 2  
**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <34  
**Inrush Current (A):** 18  
**Pulse Duration (µs):** 180

**DIMENSIONS**

**L - Length (mm):** 2278  
**H - Height (mm):** 140  
**D - Diameter (mm):** 100  
**Net Weight (kg):** 6.7