



TTP 70 L1030 TOP HF 830 HO SENSOR

TUBULAR LUMINAIRES

90474L090E04300**Light distribution**

L=1030mm

PRODUCT DESCRIPTION**Application Areas:** Public spaces, Industry, Outside**Mounting Type:** Surface mounted, Suspended, Wall mounted**Control Gear Included:** Yes**Control Gear:** LED driver 220-240VAC-50/60Hz**TTP 70 L1030 TOP HF 830 HO SENSOR****CHARACTERISTICS****Luminaire Type:** Straight line luminaire**Luminaire Module:** Individual**Insulation Class:** II**Ingress Protection (IP):** 68 (1,2m)**Mechanical Impact Protection (IK):** 10**Ambient Temperature Range (°C):**]-20, 30[**Pre-wiring / Through-wiring Included:** 1,5m long H07RN-F supply cable**Fixing System:** Clamp**Warranty (Years):** 5**Current Supply Cable Entry Point:** End cap**MATERIALS****Body Material:** Polycarbonate tube**Finishing:** Epoxy polyester powder coated**Colour:** White (W)**Glow-wire Resistance (°C):** 960**OPTICAL SYSTEM****Optical System:** TOP - Opal diffuser**Light Distribution:** Direct**Beam Angle (°):** 128**TECHNICAL DATA****Light Source:** LED**Input Power (W):** 40**Input Driver Voltage:** 220-240V-50/60Hz**Power Factor (λ):** 0,95**Luminaire Luminous Flux (lm):** 5037**Luminaire Efficacy (lm/W):** 126**Unified Glare Rating (UGR):** <28**LED Lifetime - Rated Median Useful Life:** 80.000h @ L90, B10, Ta 25°C**CCT - Correlated Colour Temperature (K):** 3000**Colour Rendering Index (CRI):** >80**Chromaticity Tolerance (MacAdam step):** <3**This Product Contains a Light Source of Energy Efficiency Class:** C**LED Module Forward Voltage Range (VF):** 34**Power Supply Dimming:** ON/OFF**Central Battery Emergency Lighting System (VDC):** 176-280**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <26**Inrush Current (A):** 33**Pulse Duration (µs):** 162**DIMENSIONS****L - Length (mm):** 1030**D - Diameter (mm):** Ø72**Net Weight (kg):** 1.94**NOTES**

- To complete the product it is necessary to order the fixation system separately;
- For suspended version it is necessary to order the suspension and the ceiling rose. Please order separately.