



**REBA 65 D/I INT L1402 SYM BGLARE DALI 840 HO**  
ALUMINIUM PROFILE SYSTEMS

**90532L005HW0000**



**Light distribution**



L=1402mm

**PRODUCT DESCRIPTION**

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care  
**Mounting Type:** Suspended  
**Control Gear Included:** No

**REBA 65 D/I INT L1402 SYM BGLARE DALI 840 HO**

**CHARACTERISTICS**

**Luminaire Type:** Straight line luminaire  
**Luminaire Module:** Individual, Middle (MID), Start / End (SRT/END)  
**Insulation Class:** I  
**Ingress Protection (IP):** 40  
**Ambient Temperature Range (°C):** ]-5, 25[  
**Warranty (Years):** 5  
**Current Supply Cable Entry Point:** Back

**MATERIALS**

**Body Material:** Extruded aluminium profile  
**Finishing:** Epoxy polyester powder coated  
**Colour:** White (W)  
**Glow-wire Resistance (°C):** 850

**OPTICAL SYSTEM**

**Optical System:** bGLARE - Microprismatic diffuser  
**Light Distribution:** Direct / Indirect  
**Beam Angle (°):** 80

**TECHNICAL DATA**

**Light Source:** LED  
**Input Power (W):** 69

**Input Driver Voltage:** 220-240V-50/60Hz  
**Power Factor (λ):** 0,96  
**Luminaire Luminous Flux (lm):** 6749  
**Luminaire Efficacy (lm/W):** 98  
**Unified Glare Rating (UGR):** <16  
**LED Lifetime - Rated Median Useful Life:** 80.000h @ L90, B10, Ta 25°C  
**CCT - Correlated Colour Temperature (K):** 4000  
**Colour Rendering Index (CRI):** >80  
**Chromaticity Tolerance (MacAdam step):** <3  
**This Product Contains a Light Source of Energy Efficiency Class:** A  
**LED Module Forward Voltage Range (VF):** 32,2  
**Power Supply Dimming:** DALI 2  
**Central Battery Emergency Lighting System (VDC):** 176-280  
**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <34  
**Inrush Current (A):** 18  
**Pulse Duration (µs):** 180

**DIMENSIONS**

**L - Length (mm):** 1402  
**W - Width (mm):** 62  
**H - Height (mm):** 71  
**Net Weight (kg):** 2.4

**NOTES**

- The indirect light diffuser is included on the product;
- To complete the product it is necessary to order the inner profile, suspension kit, current supply cable and ceiling rose. Please order separately.