



**REBA 65 D/I INT L1402 ASYM DALI 840 HO**  
ALUMINIUM PROFILE SYSTEMS

**90534L005HW0000**



**Light distribution**



L=1402mm

**PRODUCT DESCRIPTION**

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care  
**Mounting Type:** Suspended  
**Control Gear Included:** No

**REBA 65 D/I INT L1402 ASYM DALI 840 HO**

**CHARACTERISTICS**

**Luminaire Type:** Straight line luminaire  
**Luminaire Module:** Individual, Middle (MID), Start / End (SRT/END)  
**Insulation Class:** I  
**Ingress Protection (IP):** 40  
**Ambient Temperature Range (°C):** ]-5, 25[  
**Warranty (Years):** 5  
**Current Supply Cable Entry Point:** Back

**MATERIALS**

**Body Material:** Extruded aluminium profile  
**Finishing:** Epoxy polyester powder coated  
**Colour:** White (W)  
**Glow-wire Resistance (°C):** 850

**OPTICAL SYSTEM**

**Optical System:** ASYM - Asymmetric diffuser  
**Light Distribution:** Direct / Indirect  
**Beam Angle (°):** 54

**TECHNICAL DATA**

**Light Source:** LED  
**Input Power (W):** 71

**Input Driver Voltage:** 220-240V-50/60Hz

**Power Factor (λ):** 0,96

**Luminaire Luminous Flux (lm):** 6284

**Luminaire Efficacy (lm/W):** 89

**Unified Glare Rating (UGR):** <19

**LED Lifetime - Rated Median Useful Life:** 80.000h @ L90, B10, Ta 25°C

**CCT - Correlated Colour Temperature (K):** 4000

**Colour Rendering Index (CRI):** >80

**Chromaticity Tolerance (MacAdam step):** <3

**LED Module Forward Voltage Range (VF):** 32,2

**Power Supply Dimming:** DALI 2

**Central Battery Emergency Lighting System (VDC):** 176-280

**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <34

**Inrush Current (A):** 18

**Pulse Duration (µs):** 180

**This Product contains a Light Source of Energy Efficiency Class [Indirect]:** A

**DIMENSIONS**

**L - Length (mm):** 1402

**W - Width (mm):** 62

**H - Height (mm):** 71

**Net Weight (kg):** 2.77

**NOTES**

- The indirect light diffuser is included on the product;
- To complete the product it is necessary to order the inner profile, suspension kit, current supply cable and ceiling rose. Please order separately.