



CONCEPT S 35 90° LEFT D1853 HF 840 B MID/END
ARCHITECTURAL LIGHTING

90545L010EB0098



Light distribution



PRODUCT DESCRIPTION

Application Areas: Architectural, Offices, Hotels and residential, Public spaces, Retail, Art and Culture, Education, Health and care
Mounting Type: Surface mounted, Suspended
Control Gear Included: Yes
Control Gear: LED driver 220-240VAC-50/60Hz

CONCEPT S 35 90° LEFT D1853 HF 840 B MID/END

CHARACTERISTICS

Luminaire Type: Curved luminaire 1/4 90°
Luminaire Module: Middle / End (MID/END)
Luminaire Orientation: Left
Insulation Class: I
Ingress Protection (IP): 40
Ambient Temperature Range (°C):]-5, 25[
Warranty (Years): 5
Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Extruded aluminium profile
Finishing: Epoxy polyester powder coated
Colour: Black (B)
Glow-wire Resistance (°C): 960

OPTICAL SYSTEM

Optical System: bFLEX - Opal diffuser
Light Distribution: Direct
Beam Angle (°): 111

TECHNICAL DATA

Light Source: LED
Input Power (W): 44
Input Driver Voltage: 220-240V-50/60Hz
Power Factor (λ): 0,97
Luminaire Luminous Flux (lm): 4127
Luminaire Efficacy (lm/W): 94
LED Lifetime - Rated Median Useful Life: 70.000h @ L90, B10, Ta 25°C
CCT - Correlated Colour Temperature (K): 4000
Colour Rendering Index (CRI): >80
Chromaticity Tolerance (MacAdam step): <3
LED Module Forward Voltage Range (VF): 24V DC
Power Supply Dimming: ON/OFF
Maximum of luminaires by Magnetic Circuit Breaker B16: <45

DIMENSIONS

L - Length (mm): 1310
W - Width (mm): 55
H - Height (mm): 56
D - Diameter (mm): 1853
Net Weight (kg): 3.8

NOTES

- To complete the product it is necessary to order the bFLEX diffuser and the start kit. Please order separately;
- To complete the product it is necessary to order the bFLEX diffuser, start kit and body connector kit. Please order separately;
- For suspended version it is necessary to order the suspension, the current supply cable and the ceiling rose. Please order separately;
- Dimensions do not include start kit. To complete the line add 26 mm to the length;
- Create your own configurations on CONFIGURATOR.INDELAGUEGROUP.COM;
- The noise level is 20 dB, lower than the typical ambient sound levels

CONCEPT S 35 90° LEFT D1853 HF 840 B MID/END
ARCHITECTURAL LIGHTING

90545L010EB0098

recorded in environments such as libraries and reading rooms.