



**CONCEPT S 35 D/I 90° LEFT D1494 DALI 830 7 SRT**  
ARCHITECTURAL LIGHTING

**90549L008H70349**



**Light distribution**



**PRODUCT DESCRIPTION**

**Application Areas:** Architectural, Offices, Hotels and residential, Public spaces, Retail, Art and Culture, Education, Health and care  
**Mounting Type:** Suspended  
**Control Gear Included:** Yes  
**Control Gear:** LED driver 220-240VAC-50/60Hz

**CONCEPT S 35 D/I 90° LEFT D1494 DALI 830 7 SRT**

**CHARACTERISTICS**

**Luminaire Type:** Curved luminaire 1/4 90°  
**Luminaire Module:** Start (SRT)  
**Luminaire Orientation:** Left  
**Insulation Class:** I  
**Ingress Protection (IP):** 40  
**Ambient Temperature Range (°C):** ]-5, 25[  
**Warranty (Years):** 5  
**Current Supply Cable Entry Point:** Back

**MATERIALS**

**Body Material:** Extruded aluminium profile  
**Finishing:** Epoxy polyester powder coated  
**Colour:** Copper (7)  
**Glow-wire Resistance (°C):** 960

**OPTICAL SYSTEM**

**Optical System:** bFLEX - Opal diffuser  
**Light Distribution:** Direct / Indirect  
**Beam Angle (°):** 111

**TECHNICAL DATA**

**Light Source:** LED  
**Input Power (W):** 44  
**Input Driver Voltage:** 220-240V-50/60Hz  
**Power Factor (λ):** 0,97  
**Luminaire Luminous Flux (lm):** 4007  
**Luminaire Efficacy (lm/W):** 91  
**LED Lifetime - Rated Median Useful Life:** 70.000h @ L90, B10, Ta 25°C  
**CCT - Correlated Colour Temperature (K):** 3000  
**Colour Rendering Index (CRI):** >80  
**Chromaticity Tolerance (MacAdam step):** <3  
**LED Module Forward Voltage Range (VF):** 24V DC  
**Power Supply Dimming:** DALI 2  
**Maximum of luminaires by Magnetic Circuit Breaker B16:** <45

**DIMENSIONS**

**L - Length (mm):** 1057  
**W - Width (mm):** 55  
**H - Height (mm):** 56  
**D - Diameter (mm):** 1494  
**Net Weight (kg):** 4

**NOTES**

- To complete the individual product order bFLEX diffuser, start kit, current supply cable, suspension and ceiling rose. Please order separately;
- To complete the line order bFLEX diffuser, current supply cable, suspensions, start kit and body connector kit. Please order separately;
- Dimensions do not include start kit. To complete the line add 26 mm to the length;
- In order to guarantee a total uniformity of light on the ceiling, the installation must be done at a minimum distance of 500 mm;
- Create your own configurations on [CONFIGURATOR.INDEL AGUEGROUP.COM](http://CONFIGURATOR.INDEL AGUEGROUP.COM);
- The noise level is 20 dB, lower than the typical ambient sound levels

**CONCEPT S 35 D/I 90° LEFT D1494 DALI 830 7 SRT**  
ARCHITECTURAL LIGHTING

**90549L008H70349**

---

recorded in environments such as libraries and reading rooms.