


TTP 50 360 VRT L1270 TOP 840 B
TUBULAR LUMINAIRES

90555L1200B0000



Light distribution



PRODUCT DESCRIPTION

Application Areas: Public spaces, Industry, Outside
Mounting Type: Suspended
Control Gear Included: No

TTP 50 360 VRT L1270 TOP 840 B

CHARACTERISTICS

Luminaire Type: Straight line luminaire
Luminaire Module: Individual
Insulation Class: III
Ingress Protection (IP): 40
Ambient Temperature Range (°C):]-10, 25[
Warranty (Years): 5
Current Supply Cable Entry Point: End cap

MATERIALS

Body Material: Polycarbonate tube
Finishing: Epoxy polyester powder coated
Colour: Black (B)
Glow-wire Resistance (°C): 960

OPTICAL SYSTEM

Optical System: TOP - Opal diffuser
Light Distribution: Direct
Beam Angle (°): 124

TECHNICAL DATA

Light Source: LED
Input Power (W): 23
Power Factor (λ): 1

Luminaire Luminous Flux (lm): 2685
Luminaire Efficacy (lm/W): 117
Unified Glare Rating (UGR): <22
LED Lifetime - Rated Median Useful Life: 70.000h @ L80, B10, Ta 25°C
CCT - Correlated Colour Temperature (K): 4000
Colour Rendering Index (CRI): >80
Chromaticity Tolerance (MacAdam step): <3
This Product Contains a Light Source of Energy Efficiency Class: D
LED Module Forward Voltage Range (VF): 21,5-26,4
Input luminaire current (mA): 940

DIMENSIONS

L - Length (mm): 1270
D - Diameter (mm): Ø50
Net Weight (kg): 0.678

NOTES

• To complete the product it is necessary to order the current supply cable and the ceiling rose. Please order separately.