


ROFY 60 D0300 GCONTROL+ HF 830 7 HO
ARCHITECTURAL LIGHTING

90583L300E70300



Light distribution



PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care
Mounting Type: Surface mounted, Suspended, Wall mounted
Control Gear Included: Yes
Control Gear: LED driver 220-240VAC-50/60Hz

ROFY 60 D0300 GCONTROL+ HF 830 7 HO

CHARACTERISTICS

Luminaire Type: Circular luminaire
Luminaire Module: Individual
Insulation Class: I
Ingress Protection (IP): 40
Mechanical Impact Protection (IK): 4
Ambient Temperature Range (°C):]-5, 25[
Warranty (Years): 5
Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Aluminium
Frame Material: Extruded aluminium profile
Finishing: Epoxy polyester powder coated
Colour: Copper (7)
Glow-wire Resistance (°C): 650

OPTICAL SYSTEM

Optical System: gCONTROL+ - Microprismatic diffuser
Light Distribution: Direct
Beam Angle (°): 96

TECHNICAL DATA

Light Source: LED
Input Power (W): 16
Input Driver Voltage: 220-240V-50/60Hz
Power Factor (λ): 0,94
Luminaire Luminous Flux (lm): 1858
Luminaire Efficacy (lm/W): 116
Unified Glare Rating (UGR): <19
LED Lifetime - Rated Median Useful Life: 80.000h @ L90, B10, Ta 25°C
CCT - Correlated Colour Temperature (K): 3000
Colour Rendering Index (CRI): >80
Chromaticity Tolerance (MacAdam step): <3
This Product Contains a Light Source of Energy Efficiency Class: B
LED Module Forward Voltage Range (VF): 26,8
Power Supply Dimming: ON/OFF
Central Battery Emergency Lighting System (VDC): 176-280
Maximum of Luminaires by Magnetic Circuit Breaker B16: <30
Inrush Current (A): 15
Pulse Duration (µs): 100

DIMENSIONS

H - Height (mm): 85
D - Diameter (mm): 300

NOTES

• For suspended version it is necessary to order the suspension, the current supply cable and the ceiling rose. Please order separately.