


ROFY 60 /T D/I D0600 LIGHT+ HF K3 830 L LO
ARCHITECTURAL LIGHTING

90594L600EL3300



Light distribution



PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care
Mounting Type: Trimless
Control Gear Included: Yes
Control Gear: LED driver 220-240VAC-50/60Hz

ROFY 60 /T D/I D0600 LIGHT+ HF K3 830 L LO

CHARACTERISTICS

Luminaire Type: Circular luminaire
Luminaire Module: Individual
Insulation Class: I
Ingress Protection (IP): 40
Mechanical Impact Protection (IK): 4
Ambient Temperature Range (°C):]5, 25[
Warranty (Years): 5
Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Aluminium
Frame Material: Extruded aluminium profile
Finishing: Epoxy polyester powder coated
Colour: Autumn (L)
Glow-wire Resistance (°C): 650

OPTICAL SYSTEM

Optical System: LIGHT+ - Opal diffuser
Light Distribution: Direct / Indirect
Beam Angle (°): 104
Adjustable: Tilt

TECHNICAL DATA

Light Source: LED
Input Power (W): 43
Input Driver Voltage: 220-240V-50/60Hz
Power Factor (λ): 0,9
Luminaire Luminous Flux (lm): 5081
Luminaire Efficacy (lm/W): 118
Emergency Unit: 3
Unified Glare Rating (UGR): <22
LED Lifetime - Rated Median Useful Life: 80.000h @ L90, B10, Ta 25°C
CCT - Correlated Colour Temperature (K): 3000
Colour Rendering Index (CRI): >80
Chromaticity Tolerance (MacAdam step): <3
This Product Contains a Light Source of Energy Efficiency Class: B
LED Module Forward Voltage Range (VF): 92,4
Power Supply Dimming: ON/OFF
Maximum of Luminaires by Magnetic Circuit Breaker B16: <34
Inrush Current (A): 23
Pulse Duration (µs): 176
This Product contains a Light Source of Energy Efficiency Class [Indirect]: C

DIMENSIONS

H - Height (mm): 60
D - Diameter (mm): 600
D - Recess Dimensions (mm): 723
H - Recess Height (mm): 119

NOTES

• This product cannot be wall applied.